

VECTOR 100 PRO



CHARACTERISTICS:

- Camera function (2 and 4 x zoom) for easier target alignment
- Bluetooth interface for data transfer to compatible apps
- Tilt sensor for levelling and angle measurement
- Touchscreen for quick and easy operation
- Protection class IP65
- 4-line backlit display

APPLICATIONS:

- Length measurement
- Surface measurement
- Volume measurement
- Min./max. measurement
- Continuous measurement
- Indirect 3-point measurement
- Indirect 2-point measurement
- Addition/subtraction
- Measurement value memory
- Tilt sensor
- Indirect measuring via angle
- Indirect distance measurement
- Automatic distance measurement

Model

VECTOR 100 PRO

Technical details:

Item description	Laser distance meters
Dimension	115 x 50 x 25 mm
Measuring tolerance	±1.50 mm
Operating temperature	0 °C to +40 °C
Tripod adapter	1/4"
Protection class	IP65
Power supply	3 x 1.2 V Ni-Mh battery (3 x 850 mAh)
Operating time (at 20 °C)	5000 measurements
Laser class	2, DIN EN 60825-1 : 2007-10
Output power	< 1.0 mW
Wavelength	635 nm
Storage temperature	-10 °C to +60 °C
Usage area	0.2 m to 100 m

Included accessory:

- BAG VECTOR
- STRAP VECTOR
- DC VECTOR 100 PRO
- 3 x 1.2 V Ni-Mh battery (3 x 850 mAh)

