



## CHARACTERISTICS:

- Camera function (2x and 4x zoom) for easier target alignment
- Bluetooth interface for data transfer to compatible apps
- Tilt sensor for leveling and angle measurement
- Touchscreen for quick and easy operation
- Protection class IP65
- 4-line backlit display

## APPLICATIONS:

- Length measurement
- Area measurement
- Volume measurement
- Min./max. measurement
- Continuous measurement
- Indirect 3-point measurement
- Indirect 2-point measurement
- Addition/subtraction
- Measurement memory
- Tilt sensor
- Indirect measurement via angle
- Indirect distance measurement
- Automatic distance measurement

## VECTOR 100 PRO

### Model

VECTOR 100 PRO

### Technical details:

Item description	Laser distance meter
Dimensions	115 x 50 x 25 mm
Measuring tolerance	±1.50 mm
Operating temperature	0 °C to +40 °C
Tripod adapter	1/4"
Protection class	IP65
Power supply	3 x 1.2 V (AAA) Ni-Mh battery (3 x 850 mAh)
Operating time (at 20 °C)	5000 measurements
Laser class	2, DIN EN 60825-1 : 2007-10
Output power	< 1.0 mW
Wavelength	635 nm
Storage temperature	-10 °C to +60 °C
Usage area	0.2–100 m

### Included accessory:

- VECTOR belt case
- VECTOR hand strap
- VECTOR 100 PRO charging/data cable
- 3 x 1.2 V Ni-Mh battery (3 x 850 mAh)

