


FLOX



Model	PU	VP	Art. Nr.	EAN
FLOX	1		71017301	9002719035466



Characteristics

- Laser cross in front and continuous 90° laser lines allow for uninterrupted working without re-positioning the laser
- 5 mm ground clearance enables the tiles to be attached under the device
- Bright, highly visible laser lines
- Rotatable base for easy and rapid alignment of the line position
- Particularly easy and safe operation even for less experienced users

Applications

- Horizontal leveling
- Vertical leveling
- Reference lines, floor

Manufacturer

SOLA-Messwerkzeuge GmbH & Co KG
 Unteres Tobel 25
 6840 Götzis, Austria
 T +43 5523 533800
 www.sola.at, sola@sola.at

Technical details

Item description	Line lasers
Dimensions	150 x 119 x 122 mm
Leveling	Permanent floor line Self-leveling wall cross
Measuring tolerance	±0.30 mm/m (floor) / ±0.50 mm/m (wall)
Self-leveling range	±3°
Application range without handheld receiver (radius)	30 m* (floor) / 10 m* (wall)
Operating temperature	-10°C to +50 °C
Tripod adapter	1/4" + 5/8"
Protection class	IP54
Power supply	3 x 1.5 V (AA) batteries
Operating time (at 20 °C)	9 hrs (floor)/40 hrs (wall) 3 x 1.5 V (AA) batteries 24 hrs (floor)/65 hrs (wall) SOLA Li-ion battery (5200 mAh)
Laser class	2, DIN EN 60825-1 : 2014
Output power	< 1.0 mW
Wavelength	635 nm

Included accessory

- 3 x 1.5 V (AA) batteries
- BA
- LB RED
- FLOX case



SOLA-Messwerkzeuge GmbH & Co KG
 Unteres Tobel 25
 6840 Götzis, Austria
 T +43 5523 53380-0
 sola@sola.at, www.sola.at

SOLA-Messwerkzeuge GmbH & Co. KG
 Heuriedweg 69
 88131 Lindau, Germany
 T +49 8382 28585
 sola@sola.at, www.sola.de

SOLA Suisse AG
 Grenzstrasse 24
 9430 St. Margrethen, Switzerland
 T +41 71 740 1616
 info@solasuisse.ch
 www.solasuisse.ch