





CHARACTERISTICS:

- High accuracy
- Highly visible laser lines, individually switchable
- Switchable inclination function
- Rotatable through flexible 360° plumbing point for quick and easy alignment. Plumbing point is always on the rail edge.
- Permanent pulse function enables use of the optional REC LGD0 receiver in difficult visibility conditions
- REAL GREEN technology - Real. Improved. Visible.

APPLICATIONS:

- Horizontal leveling
- Inclination manual
- Vertical leveling
- 90° alignment
- Plumbing
- Aligning

ATLAS GREEN

Model

ATLAS GREEN

Technical details:

Item description	Line lasers
Dimensions	125 x 123 x 204 mm
Leveling	Self-leveling
Measuring tolerance	±0.20 mm/m
Self-leveling range	±3°
Application range without handheld receiver (radius)	25 m*
Application range with handheld receiver (radius)	80 m*
Operating temperature	-10°C to +50 °C
Tripod adapter	5/8"
Protection class	IP54
Power supply	4 x 1.5 V (AA) batteries
Operating time (at 20 °C)	6.5 hrs (all diodes)
Laser class	2, DIN EN 60825-1 : 2014
Output power	< 5.0 mW
Wavelength	510 - 525 nm

SOLA-Messwerkzeuge GmbH, Unteres Tobel 25, A-6840 Götzis, Tel: +43 (0)5523 53380-0, Fax: +43 (0)5523 53385, sola@sola.at, www.sola.at