







### **CHARACTERISTICS:**

- High accuracy
- Rotatable thanks to flexible plumbing point for quick and easy alignment
- Switchable inclination function
- Highly visible laser lines, individually switchable
- Permanent pulse function enables use of the optional REC LGD0 receiver in difficult visibility conditions
- REAL GREEN technology Real. Improved. Visible.

#### **APPLICATIONS:**

- Horizontal leveling
- Inclination manual
- Vertical leveling

# **CROSSLINE P2 GREEN**

#### Model

CROSSLINE P2 GREEN

## **Technical details:**

Item description	Line lasers
Dimensions	103 x 85 x 98 mm
Leveling	Self-leveling
Measuring tolerance	±0.20 mm/m /±0.50 mm/m (plumbing point)
Self-leveling range	±4°
Application range without handheld receiver (radius)	25 m*
Application range with handheld receiver (radius)	80 m*
Operating temperature	-10°C to +50 °C
Tripod adapter	1/4" + 5/8"
Protection class	IP54
Power supply	3 x 1.5 V (AA) batteries
Operating time (at 20 °C)	7 hrs (all diodes)
Laser class	2, DIN EN 60825-1 : 2014
Output power	< 1.0 mW
Wavelength	515 - 650 nm

# **Included accessory:**

- WH 5/8"
- 3 x 1.5 V (AA) batteries
- BA
- LB GREEN

