

# REDM DIGITAL



| Model           | Number of magnets | Length | PU | VP | Art. Nr. | EAN           |
|-----------------|-------------------|--------|----|----|----------|---------------|
| REDM 30 DIGITAL | 1                 | 30 cm  | 1  | ○  | 01735301 | 9002719043522 |
| REDM 60 DIGITAL | 3                 | 60 cm  | 1  | ☐  | 01735801 | 9002719039969 |



## Characteristics

- Measuring tolerance Solatronic module: 0.05° at 0° and 90°  
0.1° between 1° and 89°
- Bluetooth interface for the SOLA Measures app
- Adjustable inclination display in °, %, mm/m, and in/ft
- Convenient reading thanks to reversible display for inverted measurements
- Lateral magnet installation for a seamless measuring surface and maximum protection of the magnet
- Strong neodymium magnet for high adhesive force

## Applications

- Horizontal measurement
- Vertical measurement
- Angle/inclination measurement

## Manufacturer

SOLA-Messwerkzeuge GmbH & Co KG  
Unteres Tobel 25  
6840 Götzis, Austria  
T +43 5523 533800  
www.sola.at, sola@sola.at

## Technical details

|   |                                  |
|---|----------------------------------|
| Item description                          | Electronic incline spirit level  |
| Dimensions                                | 59 x 27 mm                       |
| Protection class                          | IP65                             |
| Power supply                              | 3 x 1.5 V (AAA) batteries        |
| Material                                  | Aluminum                         |
| Surface                                   | coated                           |
| Color                                     | red                              |
| Profile weight                            | 890 g/m                          |
| Measuring tolerance, standard position    | 0.50 mm/m (0.029°)               |
| Measuring tolerance, inverted measurement | 0.50 mm/m (0.029°)               |
| Number of horizontal vials                | 1                                |
| Number of vertical vials                  | 1                                |
| Special characteristic                    | Solatronic module with Bluetooth |
| Measuring surface                         | coated                           |
| Magnet                                    | Neodymium                        |
| End cap                                   | 2-c                              |
| Magnet                                    | Yes                              |

## Included accessory

- 3 x 1.5 V (AAA) batteries

**SOLA-Messwerkzeuge GmbH & Co KG**  
Unteres Tobel 25  
6840 Götzis, Austria  
T +43 5523 53380-0  
sola@sola.at, www.sola.at

**SOLA-Messwerkzeuge GmbH & Co. KG**  
Heuriedweg 69  
88131 Lindau, Germany  
T +49 8382 28585  
sola@sola.at, www.sola.de

**SOLA Suisse AG**  
Grenzstrasse 24  
9430 St. Margrethen, Switzerland  
T +41 71 740 1616  
info@solasuisse.ch  
www.solasuisse.ch