

CHARACTERISTICS:

- Easy to use: only one switch - and all laser lines are visible immediately
- Quick and precise checking of right angles and the straightness of floors and walls
- Stable magnetic fixing on the drywall ground-rails
- Rotatable through flexible 360° plumbing point for a quick and easy alignment. Plumbing point is always on the rail edge.
- SOLA Li-ion battery: full performance and a good visibility of the laser line till the very end
- Switchable pulse function for the use of the optional receiver REC LRD0 in difficult visibility conditions

APPLICATIONS:

- Horizontal leveling
- Inclination manual
- Vertical leveling
- 90° alignment
- Plumbing

QUBO PROFESSIONAL

Technical details:

Item description	Line and point laser
Dimensions	115 x 103 x 135 mm
Leveling	self-levelling
Measuring tolerance	±0.20 mm/m / ±0.30 mm/m (plumbing point)
Self-leveling range	±4°
Application range without handheld receiver (radius)	20 m*
Application range with handheld receiver (radius)	80 m*
Operating temperature	-10 °C to +50 °C (14 °F to 122 °F)
Tripod adapter	1/4" + 5/8"
Protection class	IP54
Power supply	3 x 1.5 V (AA) batteries SOLA Li-Ion battery (5200 mAh)
Operating time (at 20 °C)	12 h 3 x 1.5 V (AA) batteries 28 h SOLA Li-Ion battery (5200 mAh)
Laser class	2, DIN EN 60825-1 : 2008
Output power	< 1.0 mW
Wavelength	3 x 635 nm/1 x 650 nm