



## CROSSLINE

### Model

CROSSLINE

### Technical details:

Item description	Line laser
Dimension	120 x 65 x 105 mm
Levelling	self-levelling
Measuring tolerance	±0.20 mm/m
Self-levelling range	±4°
Application range without handheld receiver (radius)	20 m*
Application range with handheld receiver (radius)	80 m*
Operating temperature	-10 °C to +50 °C
Tripod adapter	1/4"
Protection class	IP54
Power supply	3 x 1.5 V (AA) batteries SOLA Li-Ion battery (5200 mAh)
Operating time (at 20 °C)	14 h 3 x 1.5 V (AA) batteries 30 h SOLA Li-Ion battery (5200 mAh)
Laser class	2M, DIN EN 60825-1 : 2014
Output power	< 5.0 mW
Wavelength	635 nm

### CHARACTERISTICS:

- High accuracy
- Compact, lightweight, handy
- Bright, very visible laser lines
- Rotatable base for easy and rapid alignment of the line position
- Switchable pulse function for the use of the optional receiver REC LR00 in difficult visibility conditions

### APPLICATIONS:

- Horizontal levelling
- Inclination manually
- Vertical levelling

### Included accessory:

- 3 x 1.5 V (AA) batteries
- BA
- MH
- C CROSSLINE

